

Product Data Sheet

Parquet Strip Oak Exquisite - Also known as overlays



Should you require the information on any other details please contact the sales team on **020 8501 6730** or info@wfa.uk.net

MADE IN BRITAIN



Product Details

Product Description:	9mm Parquet Strip
Wood Species:	French Oak
Construction:	Solid
Product Type:	Strip
Grade:	Exquisite
Total Thickness:	9mm
Width/s:	100 / 140 / 180mm
Length/s:	Random 1000 - 2500mm (Average 1800mm)
Wear Layer:	N/A
Core Layer:	N/A
Profile:	Square Edged
Edge Profile:	Square Edged
Finish:	Unfinished

Technical Information

Country of Manufacture:	Europe
Lamination:	N/A
Glue Line:	N/A
Standard:	BS 13227
Reaction to Fire:	BS 13501-1 Dfl-S2
Density:	710 kg/m ³
Formaldehyde Emissions:	N/A
Warmth Conduction (approx):	9mm – 0.148 W/m K
Production Tolerances;	
Width:	+/- 0.20mm
Thickness (Total):	+/- 0.20mm
Length:	+/- 0.20mm
90° Angle:	+/- 0.1 °

Grading

Maximum Size of Sound Knots:	Not Allowed - Occasional Pin Knots < 10mm
Maximum Size of Filled Knots:	Not Allowed
Filled Defects:	Not Allowed
Sap Wood:	Minimal Edge and Core Sap Wood
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain and Medullary Rays

Installation

Installation Method: Glued Pinned Floated on Underlay

Please also refer to our guidelines. ✓ ✓

NOTE: The fully bonded method of installation is recommended.

Over Underfloor Heating: When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or www.floorprotector.at

Site Conditions: 45 – 65% relative humidity & 15 – 25°C room temperature.

Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
Oiled Finish				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓
Lacquered Finish				
Bona Cleaner:		✓		
Bona Refresher:				✓

Guarantee: 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.