

# Product Data Sheet

## Stability 15 Engineered Herringbone Rustic



Should you require the information on any other details please contact the sales team on **020 8501 6730** or [info@wfa.uk.net](mailto:info@wfa.uk.net)

**MADE IN BRITAIN**



### Product Details

Product Description:	Stability 15
Wood Species:	European Oak
Construction:	Engineered
Product Type:	Herringbone
Grade:	Rustic
Total Thickness:	<b>15mm</b>
Profile:	Tongue & Grooved with Left & Right Ends
Edge Profile:	Square Edged or 1.50mm 4 Sided Micro Bevel
Finish:	Unfinished, Filled and Sanded / UV Cured Oiled - Matt, Silk or Satin / BF
Size/s:	<b>350 x 70mm *</b>
Wear Layer:	4mm Oak Wear Layer
Core Layer:	11mm Multi Layer Birch Plywood
Size/s:	<b>500 x 90mm / 600 x 120mm</b>
Wear Layer:	4mm Oak Wear Layer
Core Layer:	11mm Multi Layer Birch Plywood

### Technical Information - Birch Plywood

Country of Manufacture:	Europe
FSC®:	FSC 100% FSC-C111710
Lamination:	Hydraulic Cold Press
Glue Line:	D3 Water Based Glue
Norm:	EN 14342:2013
Reaction to Fire:	Di-s1
Density:	650 kg/m <sup>3</sup>
Formaldehyde Emissions:	Class E1 Zero Emissions
Warmth Conduction (approx):	15mm - 0.111 W/m K
Production Tolerances;	
Width:	+/- 0.2mm
Thickness (Above T&G):	+/- 0.2mm
Length:	+/- 0.2mm
90° Angle:	+/- 0.3°

**NOTE:** Sizes shown in red are non stock items, delivery will be 7 - 10 weeks, subject to finish.

\* Square edged, 20.5mm thickness, available in BF tumbled finishes only.

### Grading

Maximum Size of Sound Knots:	Up to 70mm
Maximum Size of Filled Knots:	Up to 35mm
Filled Defects:	Allowed
Filled Type:	Coloured Filler
Sap Wood:	Minimal Edge and Core Sap Wood
Cracks:	Possible
Colour Variation:	Natural Variation Allowed
Grain Variation:	Mixture of Natural Grain and Knots

### Installation

Installation Method: Glued Nailed Floated on Underlay

**Please also refer to our guidelines.** ✓

NOTE: The fully bonded method of installation is recommended.

**Over Underfloor Heating:** When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or [www.floorprotector.at](http://www.floorprotector.at)

Site Conditions: 45 - 65% relative humidity & 15 - 25°C room temperature.

### Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		
<b>Oiled Finish</b>				
Osmo Wash and Care:		✓		
Osmo Maintenance Oil:				✓
<b>Lacquered Finish</b>				
Bona Cleaner:		✓		
Bona Refresher:				✓

**Guarantee:** 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.